

BISFLOW ULTRA™

Product Description:

Bisflow Ultra™ is a highly flowable superplasticizer based on the latest polycarboxylate technology. Due to the unique flow characteristics and excellent dispersing properties, Bisflow Ultra™ is the perfect choice for any dry mix mortar mix design.

Application:

Bisflow Ultra™ is suitable for use in the following formulations:

- Tile adhesives
- Self-levelling compounds
- Non-shrink grouts
- Post tensioning grouts
- Underlayment
- GFRC mixes

Specification:

Item	Specification
Moisture content	≤3%
Solids content	≥90%
Bulk density	300-450 g/l
Ph	6.0-8.0
Water reduction rate	≥25%

Directions for use:

The recommended dose rate of Bisflow Ultra™ is 0.05% - 1% of the total cementitious material, however actual testing should be performed based on the end users application. Results may vary depending on the cement type. Bisflow Ultra™ can be added at any step of the formulation.

Disclaimer:

This document is for information purposes only. Customers are responsible for testing and confirming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

Contact

Bisley International LLC
1790 Hughes Landing Boulevard
Suite 400, The Woodlands 77380 USA
Ph: +1 (281) 506 046
Emergency telephone numbers:
+1 855 237 5573
Bisleyinterntaional.com