## Zinc Pyrithione 48% aqueous suspension Bisley International LLC

Chemwatch: **4782-12** Version No: **3.1.3.1** 

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **01/11/2019** Print Date: **12/05/2021** S.GHS.USA.EN

#### **SECTION 1 Identification**

#### **Product Identifier**

Product name	Zinc Pyrithione 48% aqueous suspension
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	Toxic, liquids, organic, n.o.s. (contains zinc pyrithione)
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Recommended use of the chemical and restrictions on use

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Bisley International LLC
Address	1790 Hughes Landing Boulevard Suite 400 The Woodlands TX 77380 United States
Telephone	+1 (844) 424 7539
Fax	Not Available
Website	www.bisley.biz
Email	compliance@bisley.biz

#### **Emergency phone number**

Association / Organisation	Bisley International LLC	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+1 855 237 5573	+61 2 9186 1132
Other emergency telephone numbers	+61 2 9186 1132	+1 855-237-5573

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

#### SECTION 2 Hazard(s) identification

### Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Classified as Dangerous Goods for transport purposes.

#### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Acute Toxicity (Oral) Category 3, Acute Toxicity (Dermal) Category 3, Acute Toxicity (Inhalation) Category 2, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1, Chronic Aquatic Hazard Category 1

#### Label elements

Hazard pictogram(s)







Signal word

Danger

Chemwatch: **4782-12** Page **2** of **11** 

Version No: **3.1.3.1** 

#### Zinc Pyrithione 48% aqueous suspension

Issue Date: **01/11/2019**Print Date: **12/05/2021** 

H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H330	Fatal if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H410	Very toxic to aquatic life with long lasting effects.

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) Prevention

Troductionally distribution		
P260	Do not breathe mist/vapours/spray.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P273	Avoid release to the environment.	
P284	Wear respiratory protection.	

#### Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P330	Rinse mouth.		
P362	Take off contaminated clothing and wash before reuse.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P391	Collect spillage.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		

#### Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
13463-41-7	48-50	zinc pyrithione
7732-18-5	50-53	water

#### **SECTION 4 First-aid measures**

#### Description of first aid measures

•	
Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  P Quickly but gently, wipe material off skin with a dry, clean cloth.  Immediately remove all contaminated clothing, including footwear.  Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.  Transport to hospital, or doctor.
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>

Issue Date: 01/11/2019 Chemwatch: 4782-12 Page 3 of 11 Version No: 3.1.3.1

#### Zinc Pyrithione 48% aqueous suspension

Print Date: 12/05/2021

- F IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor.
- Urgent hospital treatment is likely to be needed.
- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed

▶ INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

otherwise:

Treat symptomatically.

- Absorption of zinc compounds occurs in the small intestine.
- The metal is heavily protein bound.
- Elimination results primarily from faecal excretion

Ingestion

- The usual measures for decontamination (Ipecac Syrup, lavage, charcoal or cathartics) may be administered, although patients usually have sufficient vomiting not to require them
- CaNa2EDTA has been used successfully to normalise zinc levels and is the agent of choice.

#### [Ellenhorn and Barceloux: Medical Toxicology]

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

#### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

#### ADVANCED TREATMENT

▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

#### **SECTION 5 Fire-fighting measures**

#### Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances, In such an event consider:

▶ foam

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

#### Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.

#### The material is not readily combustible under normal conditions.

- ▶ However, it will break down under fire conditions and the organic component may burn.
- Not considered to be a significant fire risk
- Heat may cause expansion or decomposition with violent rupture of containers

Fire/Explosion Hazard Decomposes on heating and produces toxic fumes of: carbon dioxide (CO2)

#### Zinc Pyrithione 48% aqueous suspension

Print Date: 12/05/2021

nitrogen oxides (NOx) sulfur oxides (SOx) metal oxides other pyrolysis products typical of burning organic material. May emit poisonous fumes

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

#### Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Minor Spills Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. **Major Spills** Wear full body protective clothing with breathing apparatus Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### SECTION 7 Handling and storage

#### Precautions for safe handling Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Safe handling ▶ Use in a well-ventilated area. Prevent concentration in hollows and sumps. ▶ DO NOT allow clothing wet with material to stay in contact with skin Store in original containers. Keep containers securely sealed. Other information Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. For low viscosity materials Drums and jerricans must be of the non-removable head type. ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure. Suitable container For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging;

▶ Store away from incompatible materials and foodstuff containers.

Cans with friction closures and

low pressure tubes and cartridges

may be used.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed

#### Storage incompatibility

Avoid reaction with oxidising agents

Avoid storage with reducing agents. Avoid reaction with

metals













- Must not be stored together
- May be stored together with specific preventions
- May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

#### SECTION 8 Exposure controls / personal protection

#### Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Version No: **3.1.3.1** 

#### Zinc Pyrithione 48% aqueous suspension

Issue Date: 01/11/2019
Print Date: 12/05/2021

#### Not Available

#### Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Zinc Pyrithione 48% aqueous suspension	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
zinc pyrithione	Not Available		Not Available	
water	Not Available		Not Available	

#### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
zinc pyrithione	E ≤ 0.01 mg/m³		
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

#### **Exposure controls**

## Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Personal protection













## Eye and face protection

- Safety glasses with side shields.
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

#### Skin protection

#### See Hand protection below

- $\mbox{\ensuremath{\,\triangleright\,}}$  Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber NOTE:

## Hands/feet protection

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care.

#### Body protection

See Other protection below

#### Other protection

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

#### Respiratory protection

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

#### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance	White aqueous dispersion with a mild odour; dispersible in water.				
Physical state	Liquid	Relative density (Water = 1)	Not Available		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	Not Available	Decomposition temperature	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)	100 approx	Molecular weight (g/mol)	Not Applicable		

Chemwatch: 4782-12 Page 6 of 11 Issue Date: 01/11/2019
Version No: 3.1.3.1 Print Date: 12/05/2021

#### Zinc Pyrithione 48% aqueous suspension

Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

Ingestion

Chronic

Information on toxicological effects

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.
There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can

# cause further lung damage. Inhalation of pyrithione dust may cause headache, nausea and vomiting. Animals exposed by inhalation to the sodium salt showed reduced weight gain, reddened lungs, red material around the eye and nose, lethargy, tremor, inco-ordination, convulsions and paralysis of the hind legs before dying 10-14 days later.

Welding or flame cutting of metals with zinc or zinc dust coatings may result in inhalation of zinc oxide fume; high concentrations of zinc oxide fume may result in "metal fume fever"; also known as "brass chills", an industrial disease of short duration. [I.L.O] Symptoms include malaise, fever, weakness, nausea and may appear quickly if operations occur in enclosed or poorly ventilated areas.

## Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.

Pyridinethione is toxic to the nervous system, and animal testing has shown diminished grip strength and progressive nerve damage to the extremities.

Soluble zinc salts produce irritation and corrosion of the alimentary tract with pain, and vomiting. Death can occur due to insufficiency of food intake due to severe narrowing of the oesophagus and pylorus.

Severe exposure to pyrithione due to swallowing is unlikely as it strongly induces vomiting. Animal testing shows a single dose of sodium pyrithione, regardless of dose, can cause paralysis of the rear extremities and convulsions, as well as detachment of the retina.

#### Skin contact with the material may produce toxic effects; systemic effects may result following absorption.

This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition

Nerve inflammation with altered sensation and muscle weakness were associated with prolonged use of a shampoo (Head and Shoulders)

If applied to the eyes, this material causes severe eye damage.

# Skin Contact containing 2% zinc pyrithione. Muscle weakness disappeared 3 months after stopping the use of the shampoo and altered sensation improved by about 75% in about 2 years. Reversible burning sensation, skin redness, swelling and fluid accumulation on the skin have been observed, worse with repeated application. After topical application in rats, muscle damage and paralysis of the hind limbs were also observed. Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

## Eye Instillation of 1ml of a 40% solution of sodium pyrithione in water, into the eyes of rabbits produced mild, transient clouding of the cornea and mild reddening in the conjunctiva.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Exposure may aggravate diseases of muscles and nerves. Prolonged contact may cause allergic dermatitis in sensitive people, followed by photosensitivity. Chronic exposure may result in wasting of muscles, and damage to peripheral nerves. Animal testing in dogs only showed irreversible eye damage and blindness.

Welding or flame cutting of metals with zinc or zinc dust coatings may result in inhalation of zinc oxide fume; high concentrations of zinc oxide fume may result in "metal fume fever"; also known as "brass chills", an industrial disease of short duration. [I.L.O] Symptoms include malaise, fever, weakness, nausea and may appear quickly if operations occur in enclosed or poorly ventilated areas.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Data from experimental studies indicate that pyridines represent a potential cause of cancer in man. They have also been shown to cross the placental barrier in rats and cause premature delivery, miscarriages and stillbirths.

Chemwatch: 4782-12 Page 7 of 11 Version No: 3.1.3.1

#### Zinc Pyrithione 48% aqueous suspension

Issue Date: 01/11/2019 Print Date: 12/05/2021

Zinc Pyrithione 48% aqueous	TOXICITY	IRRITATION	
suspension	Not Available	Not Available	
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 1 mg/48h Irritant	
zinc pyrithione	Inhalation(Rat) LC50; 0.14 mg/L4h <sup>[2]</sup>		
	Oral(Rat) LD50; 221 mg/kg <sup>[1]</sup>		
	тохісіту	IRRITATION	
water	Oral(Rat) LD50; >90000 mg/kg <sup>[2]</sup>	Not Available	
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		
ZINC PYRITHIONE	Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).  NOAEL: 11.0 mg/kg/day cynomolgus monkey * [* = Arch Chemical] Acute pulmonary oedema, dyspnea, weight loss or decreased weight gain, recordings from specific areas of the CNS, mydriasis, somnolence, changes in motor activity, recording from peripheral motor nerve, muscle weakness, spastic paralysis, reproductive system tumours, retinal changes, diarrhoea, foetoxicity, specific developmental abnormalities (musculoskeletal system, central nervous system, effects on newborn, foetolethality recorded.		
Zinc Pyrithione 48% aqueous suspension & WATER	No significant acute toxicological data identified in literature search.		
Zinc Pyrithione 48% aqueous suspension & ZINC	Animal testing shows that pyrithiones at sufficient doses can cause vomiting, bleeding of the mucous membranes of the stomach and weight loss and anaemia and paralysis at very high doses, and in extreme cases may be lethal. Although it is very poorly absorbed through skin, dermal		

nervous system. Pyrithiones may reduce fertility and cause an increase in birth defects. **Acute Toxicity** Carcinogenicity × Skin Irritation/Corrosion Reproductivity × Serious Eye Damage/Irritation STOT - Single Exposure Respiratory or Skin × × STOT - Repeated Exposure sensitisation X Mutagenicity **Aspiration Hazard** 

Legend:

exposure at very high doses can potentially cause similar effects. Chronic exposure, in animal testing, has been shown to potentially damage the

X - Data either not available or does not fill the criteria for classification

- Data available to make classification

#### **SECTION 12 Ecological information**

suspension & ZINC

**PYRITHIONE** 

Zinc Pyrithione 48% aqueous suspension	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1440h	Fish	52-180	7
zinc pyrithione	NOEC(ECx)	672h	Crustacea	<0.001mg/L	4
	EC50	72h	Algae or other aquatic plants	0.001mg/L	4
	EC50	48h	Crustacea	<0.001mg/L	4
	LC50	96h	Fish	<0.001mg/L	4
	EC50	96h	Algae or other aquatic plants	<0.001mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Source
water	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from	IUCLID Toxicity Data 2. Europe EC	CHA Registered Substances - Ecotoxicological Informati	on - Aquatic Toxicity 3. E	PIWIN Su

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Sodium pyrithione (NaPT), zinc pyrithione (ZnPT), and copper pyrithione (CuPT) are antimicrobial agents used in cosmetics and fuel industries, as well as in mining industry due to their metal chelating properties.

Environmental Fate: Leaching, from painted hulls, of these compounds is the major mode of transport into to the water environment. Based on the physico-chemical properties of these compounds, CuPT is less soluble to water than ZnPT biocide indicating that ZnPT will leach faster than CuPT. ZnPT in the environment is likely to degrade in the water column even before reaching the sediment and it may transchelate to less soluble CuPT.

For Zinc and its Compounds: BCF: 4 to 24,000.

Environmental Fate: Zinc is capable of forming complexes with a variety of organic and inorganic groups and is an essential nutrient present in all organisms.

Atmospheric Fate: Zinc concentrations in the air are relatively low, except near industrial sources, such as smelters. There is no estimate for the atmospheric lifetime of zinc, but, since zinc is transported long distances in air, its lifetime in air is at least on the order of days.

Chemwatch: **4782-12**Version No: **3.1.3.1** 

Page 8 of 11

#### Zinc Pyrithione 48% aqueous suspension

Issue Date: 01/11/2019 Print Date: 12/05/2021

For Pyridine and its Derivatives:

Environmental Fate: As molecular weight/substitution increase in the pyridine category, greater distribution to water and soil, and less to air, is predicted.

Atmospheric Fate: The lower weight pyridine, piperidine, is expected to be rapidly degraded by UV light in the atmosphere, with an estimated half-life of < 1 day. Higher molecular weight pyridines are expected to be broken down by sunlight, (photodegrades), more slowly, (half-lives ranging from 10-30 days). Lutidines and collidines are expected to photodegrade even more slowly.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
zinc pyrithione	LOW (BCF = 240)

#### Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

#### Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- ► Reuse
- ► Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

#### **SECTION 14 Transport information**

#### **Labels Required**



Marine Pollutant



#### Land transport (DOT)

UN number	2810		
UN proper shipping name	Toxic, liquids, organic, n.o.s. (contains zinc pyrithione)		
Transport hazard class(es)	Class 6.1 Subrisk Not Applicable		
Packing group			
Environmental hazard	Environmentally hazardous		
Special precautions for user	Hazard Label 6.1  Special provisions IB2, T11, TP2, TP13, TP27		

Version No: **3.1.3.1** 

#### Zinc Pyrithione 48% aqueous suspension

Issue Date: **01/11/2019**Print Date: **12/05/2021** 

UN number	2810			
UN proper shipping name	Toxic liquid, organic, n.o.s. * (contains zinc pyrithione)			
	ICAO/IATA Class	6.1		
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable		
	ERG Code	6L		
Packing group	II			
Environmental hazard	Environmentally hazardo	ous		
	Special provisions		A3 A4 A137	
	Cargo Only Packing Ir	nstructions	662	
	Cargo Only Packing Ir			
Special precautions for user		Qty / Pack	662	
Special precautions for user	Cargo Only Maximum	Qty / Pack Packing Instructions	662 60 L	
Special precautions for user	Cargo Only Maximum Passenger and Cargo Passenger and Cargo	Qty / Pack Packing Instructions	662 60 L 654	

#### Sea transport (IMDG-Code / GGVSee)

UN number	2810		
UN proper shipping name	TOXIC LIQUID, ORGANIC, N.O.S. (contains zinc pyrithione)		
Transport hazard class(es)	IMDG Class 6.1 IMDG Subrisk Not Applicable		
Packing group			
Environmental hazard	Marine Pollutant		
Special precautions for user	EMS Number F-A , S-A Special provisions 274 Limited Quantities 100 mL		

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
zinc pyrithione	Not Available
water	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
zinc pyrithione	Not Available
water	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

### zinc pyrithione is found on the following regulatory lists

US CWA (Clean Water Act) - Priority Pollutants	
US CWA (Clean Water Act) - Toxic Pollutants	
US EPA Integrated Risk Information System (IRIS)	

US EPCRA Section 313 Chemical List

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

### water is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### **Federal Regulations**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Section 311/312 hazard categories

Coolin of No.12 hazara dategories		
Flammable (Gases, Aerosols, Liquids, or Solids)		
Gas under pressure	No	
Explosive	No	
Self-heating	No	
Pyrophoric (Liquid or Solid)		
Pyrophoric Gas	No	

Chemwatch: 4782-12 Page 10 of 11 Issue Date: 01/11/2019 Version No: 3.1.3.1 Print Date: 12/05/2021

#### Zinc Pyrithione 48% aqueous suspension

Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	Yes
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	
Serious eye damage or eye irritation	
Specific target organ toxicity (single or repeated exposure)	
Aspiration Hazard	No
Germ cell mutagenicity	
Simple Asphyxiant	
Hazards Not Otherwise Classified	

#### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

#### State Regulations

#### US. California Proposition 65

None Reported

#### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (zinc pyrithione; water)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	No (zinc pyrithione)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

#### **SECTION 16 Other information**

Revision Date	01/11/2019
Initial Date	26/04/2012

#### **SDS Version Summary**

Version	Date of Update	Sections Updated		
3.1.2.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification		
3.1.3.1	10/05/2021	Regulation Change		

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

Chemwatch: 4782-12 Page 11 of 11 Issue Date: 01/11/2019 Version No: 3.1.3.1

#### Zinc Pyrithione 48% aqueous suspension

Print Date: 12/05/2021

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.