

# Product Information

## PDMS 350

### Product Description:

PDMS 350 is a colorless transparent liquid composed of polymethylsiloxane, also known as dimethicone. It is a surfactant that is essentially non-toxic and has excellent dielectric properties. It contains organic methyl groups and inorganic siloxane bonds providing it excellent chemical and thermal stability. PDMS products are available in a variety of viscosity ranges.

### Applications:

PDMS 350 is widely used as a lubricant, mechanical fluid, mold release agent, anti-foam agent, polish, wetting agent insulating and damping fluid. It is used in variety of industries such as food, personal care, metal die casting, plastics, rubbers, electronics and paints and coatings

### Chemical Formula:

$(C_2H_6OSi)_n$

### CAS No. :

9006-65-6

### Specifications:

Parameters (units)	Specifications
Appearance	Colorless transparent liquid
Specific gravity at 25 °C	0.962 - 0.972
Refractive index at 25 °C	1.4020 - 1.4040
Viscosity (cSt)	350 ± 20
Flash point (°C)	≥ 315
Ignition point (C)	> 400
Freezing point, approx. (°C)	- 55

\*% denoted represents wt/wt %, unless noted otherwise

Bisley International LLC  
1790 Hughes Landing Boulevard Suite 400  
The Woodlands 77380 TX USA  
Phone number: +1 (844) 424 7539  
Emergency telephone number: +1 855 237 5573

[bisleyinternational.com](http://bisleyinternational.com)

Copyright 2021 Bisley & Co. Pty Ltd. All rights reserved



## Packaging:

Material is available in 190 kg steel drums and 950 kg IBCs. Further packaging options may be available upon inquiry.

## Storage:

Product should be stored in a dry place away from direct sunlight in sealed, original packaging. In the original unopened packaging, PDMS 350 has a shelf life of 36 months when stored at ambient temperatures.

## Safety:

For further safety information refer to product SDS available from your Bisley International contact.

Disclaimer: This document is for information purpose only. Customers are responsible for testing and conforming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

### Global Headquarters

#### Sydney, Australia

Bisley & Company  
Level 12, Tower B Citadel Towers  
799 Pacific Highway  
Chatswood NSW 2067 Australia  
Phone: +61 2 8905 4200  
Fax: +61 2 8905 4238  
Email: [australia@bisley.biz](mailto:australia@bisley.biz)

### Jakarta, Indonesia

PT Bisindo Kencana  
Puri Indah  
Financial Tower  
9<sup>th</sup> Floor, Unit 09 Jalan Puri  
Lingkar Dalam Blok  
T8 Jakarta Barat 11610  
Indonesia  
Phone: +6221 530 7287

### Bangkok, Thailand

Bisley Asia (Thailand) Co. Ltd.  
Mahatun Plaza Building 18th Floor  
888/186 Ploenchit Road  
Lumpini, Pathumwan  
Bangkok 10330  
Thailand  
Phone: +66 0 2689 6396  
Fax: +66 0 2689 6394

### Kuala Lumpur, Malaysia

Bisley Asia (M) Sdn Bhd  
Co. Reg. No.:199201002123  
(233627-U)  
Suite 20-01 & 20-02B,  
Level 20, The Pinnacle,  
Persiaran Lagoon, 47500  
Bandar Sunway, Subang Jaya Selangor,  
Malaysia  
Tel: +603-56244287/4289  
Fax: +603-56244201

### Dubai, United Arab Emirates

Bisley Chemicals Trading LLC  
1802 B2B Office Tower  
Business Bay  
PO Box 9298  
Dubai United Arab Emirates  
Phone: +971 4 3310088  
+971 4 3310111  
Fax: +971 4 3310099

### USA and Canada

Bisley International LLC  
1790 Hughes Landing Boulevard  
Suite 400  
The Woodlands 77380 TX USA  
Phone: +1 (844) 424 7539  
Emergency telephone number:  
+1 855 237 5573  
Email: [international@bisley.biz](mailto:international@bisley.biz)

Bisley International LLC  
1790 Hughes Landing Boulevard Suite 400  
The Woodlands 77380 TX USA  
Phone number: +1 (844) 424 7539  
Emergency telephone number: +1 855 237 5573

[bisleyinternational.com](http://bisleyinternational.com)

Copyright 2021 Bisley & Co. Pty Ltd. All rights reserved

