Product Information

Citric Acid Monohydrate

Product Description:

This product is composed of odorless white granulated crystals of a very high purity citric acid monohydrate. Citric acid monohydrate is very soluble in water and has excellent buffering and weakly acidic properties in solution. It is soluble in organic solvents such as ethanol and ether. This product conforms to the EP, USP, FCC and Codex Alimentarius requirements.

Applications:

Citric acid monohydrate is used as a retarder in concrete and gypsum mixtures. It is used as a dispersant in oil & gas well cementing systems. It is used in the food industry as an acidifier, stabilizer, flavouring and chelating agent. It can be used as a soldering flux, in the passivation of steel and in detergent manufacture.

Chemical Formula:

 $C_6H_8O_7 \cdot H_2O$

CAS No.:

5949-29-1

Specifications

Parameters (units)	Specifications
Appearance	Granulated crystals
Assay (%)	99.5 - 100
Moisture content (%)	8.10 - 8.70
Sulfated ash (%)	≤ 0.05
Sulfate (ppm)	< 30
Oxalate (ppm)	≤ 100
Cadmium (ppm)	< 0.1
Chromium (ppm)	< 1
Calcium (ppm)	< 10
Nickel (ppm)	< 1
Iron (ppm)	< 1
Chloride (ppm)	< 5
Aluminium (ppm)	< 0.2
Barium (ppm)	< 1

Parameters (units)	Specifications
Mercury (ppm)	< 1
Arsenic (ppm)	< 1
Lead (ppm)	< 0.5
Copper (ppm)	< 1
Zinc (ppm)	< 1
Magnesium (ppm)	< 1
Pesticide residue (ppb)	≤ 10
Microbiology analysis, total count (cfu/g mL)	< 100
Yeast (cfu/g mL)	< 1000
E. coli (cfu/g mL)	< 10
Enterobacteriaceae (cfu/g mL)	< 10
Particle size, residue retained on 4000 µm mesh (%)	≤ 10
Particle size, residue passed through 150 µm mesh (%)	≤ 10

Bisley International LLC 1790 Hughes Landing Boulevard Suite 400 The Woodlands 77380 TX USA Phone number: +1 (844) 424 7539

Emergency telephone number: +1 855 237 5573





Packaging:

Material is available in 25 kg polyethylene bags and 1000 kg polypropylene bags. Further packaging options may be available upon enquiry.

Storage:

Product should be stored in a dry place at room temperature (10 $^{\circ}$ C - 30 $^{\circ}$ C) away from direct sunlight in sealed, original packaging. The shelf life for this product is 24 months.

Safety:

For further safety information refer to product SDS available from your Bisley International contact.

Disclaimer: This document is for information purpose only. Customers are responsible for testing and conforming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

Global Headquarters

Sydney, Australia

Bisley & Company Level 12, Tower B Citadel Towers 799 Pacific Highway Chatswood NSW 2067 Australia

Phone: +61 2 8905 4200 Fax: +61 2 8905 4238 Email: australia@bisley.biz

Kuala Lumpur, Malaysia

Bisley Asia (M) Sdn Bhd Co. Reg. No.:199201002123 (233627-U) Suite 20-01 & 20-02B, Level 20, The Pinnacle, Persiaran Lagoon, 47500 Bandar Sunway, Subang Jaya Selangor,

Malaysia

Tel: +603-56244287/4289 Fax: +603-56244201 Jakarta, Indonesia

PT Bisindo Kencana Puri Indah Financial Tower 9th Floor, Unit 09 Jalan Puri Lingkar Dalam Blok T8 Jakarta Barat 11610 Indonesia

Phone: +6221 530 7287

Dubai, United Arab Emirates

Bisley Chemicals Trading LLC 1802 B2B Office Tower Business Bay PO Box 9298 Dubai United Arab Emirates Phone: +971 4 3310088

+971 4 3310111 Fax: +971 4 3310099 Bangkok, Thailand

Bisley Asia (Thailand) Co. Ltd.
Mahatun Plaza Building 18th Floor
888/186 Ploenchit Road
Lumpini, Pathumwan
Bangkok 10330
Thailand

Phone: +66 0 2689 6396 Fax: +66 0 2689 6394

USA and Canada

Bisley International LLC 1790 Hughes Landing Boulevard Suite 400 The Woodlands 77380 TX USA Phone: +1 (844) 424 7539 Emergency telephone number:

+1 855 237 5573

Email: international@bisley.biz

Bisley International LLC 1790 Hughes Landing Boulevard Suite 400 The Woodlands 77380 TX USA Phone number: +1 (844) 424 7539 Emergency telephone number: +1 855 237 5573

bisleyinternational.com

