

# Product Information

## Sensocure 942

### Product Description:

Sensocure 942 is a cyclo-aliphatic amine containing, low viscosity and low color epoxy resin curing agent. It has superb water and corrosion resistance properties. It has a long pot life, dries fast and provides excellent adhesion for metal and mineral substrates. The addition of Sensocure 942 to epoxy results in the formation of epoxy amine crosslinks that cure and harden the resin.

### Applications:

Sensocure 942 is a universal curing agent for light color casting, laminating of surfaces, self-levelling floors and as a coating resin. It can be used as an adhesive, mortar and primer epoxies.

### Specifications

Parameters (units)	Specifications
Appearance	Clear liquid
Active chemical	Isophrone diamine
Active content, approx. (%)	100 %
Color (APHA)	≤ 8
Viscosity, Brookfield at 25 °C (mPa.s)	15 - 25
Amine value (mg KOH/g)	650 - 670
PHR, with liquid epoxy resin EE 190	21
Specific gravity, at 20 °C	Approx. 0.920

Bisley International LLC  
1790 Hughes Landing Boulevard Suite 400  
The Woodlands 77380 TX USA  
Phone number: +1 (844) 424 7539  
Emergency telephone number: +1 855 237 5573

[bisleyinternational.com](http://bisleyinternational.com)

Copyright 2021 Bisley & Co. Pty Ltd. All rights reserved



## Packaging:

Material packaging options are available upon enquiry.

## Storage:

Product should be stored in a dry place away from direct sunlight in sealed, original packaging. This product should be stored at a temperature between 5 °C and 35 °C. It has a shelf life of 1 year.

## Safety:

For further safety information refer to product SDS available from your Bisley International contact.

Disclaimer: This document is for information purpose only. Customers are responsible for testing and conforming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

### Global Headquarters

#### Sydney, Australia

Bisley & Company  
Level 12, Tower B Citadel Towers  
799 Pacific Highway  
Chatswood NSW 2067 Australia  
Phone: +61 2 8905 4200  
Fax: +61 2 8905 4238  
Email: [australia@bisley.biz](mailto:australia@bisley.biz)

### Jakarta, Indonesia

PT Bisindo Kencana  
Puri Indah  
Financial Tower  
9<sup>th</sup> Floor, Unit 09 Jalan Puri  
Lingkar Dalam Blok  
T8 Jakarta Barat 11610  
Indonesia  
Phone: +6221 530 7287

### Bangkok, Thailand

Bisley Asia (Thailand) Co. Ltd.  
Mahatun Plaza Building 18th Floor  
888/186 Ploenchit Road  
Lumpini, Pathumwan  
Bangkok 10330  
Thailand  
Phone: +66 0 2689 6396  
Fax: +66 0 2689 6394

### Kuala Lumpur, Malaysia

Bisley Asia (M) Sdn Bhd  
Co. Reg. No.:199201002123  
(233627-U)  
Suite 20-01 & 20-02B,  
Level 20, The Pinnacle,  
Persiaran Lagoon, 47500  
Bandar Sunway, Subang Jaya Selangor,  
Malaysia  
Tel: +603-56244287/4289  
Fax: +603-56244201

### Dubai, United Arab Emirates

Bisley Chemicals Trading LLC  
1802 B2B Office Tower  
Business Bay  
PO Box 9298  
Dubai United Arab Emirates  
Phone: +971 4 3310088  
+971 4 3310111  
Fax: +971 4 3310099

### USA and Canada

Bisley International LLC  
1790 Hughes Landing Boulevard  
Suite 400  
The Woodlands 77380 TX USA  
Phone: +1 (844) 424 7539  
Emergency telephone number:  
+1 855 237 5573  
Email: [international@bisley.biz](mailto:international@bisley.biz)

Bisley International LLC  
1790 Hughes Landing Boulevard Suite 400  
The Woodlands 77380 TX USA  
Phone number: +1 (844) 424 7539  
Emergency telephone number: +1 855 237 5573

[bisleyinternational.com](http://bisleyinternational.com)

Copyright 2021 Bisley & Co. Pty Ltd. All rights reserved

