# **BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89**

# **Bisley International LLC**

Chemwatch: 4076-06 Version No: 5.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

### Chemwatch Hazard Alert Code: 2

Issue Date: 11/11/2019 Print Date: 17/11/2021 S.GHS.USA.EN

### **SECTION 1 Identification**

Proc	luct	Identifier	
------	------	------------	--

i roddot idontinioi	
Product name	BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89
Chemical Name	5,5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione
Chemical formula	C4H2N4S6
Other means of identification	Not Available
CAS number	72676-55-2

### Recommended use of the chemical and restrictions on use

### Relevant identified uses

Lube oil or grease additive. Extreme pressure additive for greases.or used as cross-linking agent for polyacrylate elastomers.

2,5-Dimercapto-1,3,4-thiadiazole (syn: DMcT; bismuthiol I) and its derivatives are used in synthesising salts of strong bases, heavy metal salts, and polymers; as ingredients in flame and scorch retardants; in cross linking halogenated polymers; as additives in lubricating oils and greases; as corrosion inhibitors; in electrode compositions; in photography; as adhesion improvers; as intermediates or starting materials for pharmaceuticals and dyes; as chelating agents used to determine metals in samples; in purifying and treating waste; and as biocides. Intermediate.

A privileged structure (capable of binding to multiple receptors with high affinity).

In order to be considered privileged, a substructure should represent a molecule's core element and make up a significant portion of its total mass.

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Bisley International LLC
Address	1790 Hughes Landing Boulevard Suite 400 The Woodlands TX 77380 United States
Telephone	+1 (844) 424 7539
Fax	Not Available
Website	www.bisley.biz
Email	compliance@bisley.biz

### **Emergency phone number**

Association / Organisation	Bisley International LLC	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+1 855 237 5573	+61 2 9186 1132
Other emergency telephone numbers	+61 2 9186 1132	+1 855-237-5573

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

### SECTION 2 Hazard(s) identification

### Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Not classified as Dangerous Goods for transport purposes.

### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Sensitisation (Skin) Category 1

### Label elements

Version No: 5.1

Page 2 of 9

### **BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89**

Issue Date: 11/11/2019 Print Date: 17/11/2021

Hazard pictogram(s)



Signal word

Warning

### Hazard statement(s)

H317

May cause an allergic skin reaction.

### Hazard(s) not otherwise classified

Not Applicable

### Precautionary statement(s) Prevention

P280	Wear protective gloves and protective clothing.
P261	Avoid breathing dust/fumes.
P272	Contaminated work clothing must not be allowed out of the workplace.

### Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

### Precautionary statement(s) Storage

Not Applicable

### Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

### Substances

CAS No	%[weight]	Name
72676-55-2	>98	5.5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione

# Mixtures

See section above for composition of Substances

# **SECTION 4 First-aid measures**

### Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If dust is inhaled, remove from contaminated area.</li> <li>Encourage patient to blow nose to ensure clear passage of breathing.</li> <li>If irritation or discomfort persists seek medical attention.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

# Most important symptoms and effects, both acute and delayed

See Section 11

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Fire-fighting measures**

# Extinguishing media

- Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Chemwatch: 4076-06

Page 3 of 9

Version No: 5.1

### **BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89**

Issue Date: 11/11/2019 Print Date: 17/11/2021

### Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

### Special protective equipment and precautions for fire-fighters

### Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses
- Use water delivered as a fine spray to control fire and cool adjacent area.

# Fire/Explosion Hazard

• Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions.

Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions).

Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion.

Combustion products include:

carbon monoxide (CO) carbon dioxide (CO2) nitrogen oxides (NOx) sulfur oxides (SOx)

other pyrolysis products typical of burning organic material.

May emit corrosive fumes

### **SECTION 6 Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

### Minor Spills

- Clean up all spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- ▶ Use dry clean up procedures and avoid generating dust.

### Major Spills

# Moderate hazard. • CAUTION: Advise personnel in area.

- Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

### Precautions for safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

  Safe handling
  Organic powders when finely divided over a
  - Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)
  - Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.
  - Establish good housekeeping practices.
  - ▶ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.

### Other information

- ► Store in original containers.
- Keep containers securely sealed.
- ► Store in a cool, dry area protected from environmental extremes.
- ► Store away from incompatible materials and foodstuff containers.

# Conditions for safe storage, including any incompatibilities

### Suitable container

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- ▶ Polyliner drum.
- Packing as recommended by manufacturer.

### Storage incompatibility

Avoid reaction with oxidising agents





Х











X — Must not be stored together

Chemwatch: 4076-06

Version No: 5.1

Page 4 of 9

**BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89** 

Issue Date: 11/11/2019 Print Date: 17/11/2021

May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

### SECTION 8 Exposure controls / personal protection

### Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

### **Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
5,5'-dithiobis-1,3,4-thiadiazole- 2(3H)-thione	Not Available	Not Available

### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
5,5'-dithiobis-1,3,4-thiadiazole- 2(3H)-thione	D	> 0.01 to ≤ 0.1 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

#### Exposure controls

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

### Personal protection











# Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

### Skin protection

### See Hand protection below

### NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Hands/feet protection

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polvchloroprene.
- nitrile rubber.
- butyl rubber.

### Body protection

# Overalls.

### Other protection

- P.V.C apron.
- Barrier cream.
- ▶ Skin cleansing cream

See Other protection below

### Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection

Page 5 of 9

**BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89** 

Issue Date: 11/11/2019
Print Date: 17/11/2021

### program.

- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

### **SECTION 9 Physical and chemical properties**

Information on basic physical and chemical properties		
Appearance	Yellow powder; does not mi	

Appearance	Yellow powder; does not mix well with water. Contains small amount of mineral oil to assist in controlling dusts.		
Physical state	Divided Solid	Relative density (Water = 1)	2.09 g/cm3
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	153	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	298.44
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

Inhaled

Skin Contact

Chronic

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal
models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an
occupational setting.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.

Ingestion	Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health
ingestion	of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident.

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye In animal tests irritation cleared after seven days.

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.

5,5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione

TOXICITY	IRRITATION
Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: mild *

Chemwatch: **4076-06** 

Version No: 5.1

# Page 6 of 9 BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89

Issue Date: 11/11/2019
Print Date: 17/11/2021

	Oral(Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin: Primary Irritation Score *
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute to:     specified data extracted from RTECS - Register of Toxic Effect of chemic	

for Vanlube 829

The following information refers to contact allergens as a group and may not be specific to this product.

### 5,5'-DITHIOBIS-1,3,4-THIADIAZOLE-2(3H)-THIONE

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria,

eczena involves a cen-mediated (1 fyriphicoyes) infinitire reaction of the delayed type. Other antegic skill reactions, e.g. contact uticana, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.

2,5-Dimercapto-1,3,4-thiadiazole (DMcT) may cause eye irritation, chemical conjunctivitis, skin irritation, respiratory tract irritation, and

gastrointestinal irritation, including nausea, vomiting, and diarrhea. During acute inhalation exposure, it can produce irritation to mucous membranes and the upper respiratory tract, and upon short-term exposure, it can cause skin irritation and severe eye irritation. DMcT was one of 43 compounds tested in 16 men as an antidote to the skin vesicant lewisite, an arsenic compound. It was not an effective decontaminant of lewisite, producing 14 erythemas compared to 7 induced by 2,3-dimercaptopropanol.

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment

Acute Toxicity	×	Carcinogenicity	X
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

— Data either not available or does not fill the criteria for classification

— Data available to make classification

### **SECTION 12 Ecological information**

### **Toxicity**

mg/L

	Endpoint	Test Duration (hr)	Species	Value	Source
5,5'-dithiobis-1,3,4-thiadiazole-	NOEC(ECx)	48h	Crustacea	1.4mg/l	2
2(3H)-thione	EC50	72h	Algae or other aquatic plants	20mg/l	2
	EC50	48h	Crustacea	3mg/l	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite				

Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

for 2,5-dimercapto-1,3,4-thiadiazole and its derivatives:
2,5-bis(tert-nonyldithio)-1,3,4-thiadiazole (also known as Amoco 158) is not be readily biodegradable; it biodegraded by 2-5% in 28 days using the biochemical oxygen demand test

and high-performance liquid chromatography. In fathead minnows (Pimephales promelas), a 96-hour LC50 of >1000 mg/L was determined; the no observed effect level was 1000

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

# Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

### Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

# **SECTION 13 Disposal considerations**

# Waste treatment methods

Product / Packaging disposal

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

### Otherwise:

# If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

Version No: **5.1** 

### **BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89**

Issue Date: 11/11/2019
Print Date: 17/11/2021

- Reduction
- Reuse
- ► Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.

# **SECTION 14 Transport information**

### Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
5,5'-dithiobis-1,3,4-thiadiazole- 2(3H)-thione	Not Available

### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
5,5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione	Not Available

### **SECTION 15 Regulatory information**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

5,5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

### **Federal Regulations**

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

# Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)		
Gas under pressure	No	
Explosive	No	
Self-heating	No	
Pyrophoric (Liquid or Solid)	No	
Pyrophoric Gas	No	
Corrosive to metal	No	
Oxidizer (Liquid, Solid or Gas)	No	
Organic Peroxide	No	
Self-reactive	No	
In contact with water emits flammable gas	No	
Combustible Dust	No	
Carcinogenicity	No	
Acute toxicity (any route of exposure)	No	
Reproductive toxicity	No	
Skin Corrosion or Irritation	No	
Respiratory or Skin Sensitization		
Serious eye damage or eye irritation	No	
Specific target organ toxicity (single or repeated exposure)	No	
Aspiration Hazard	No	
Germ cell mutagenicity		
Simple Asphyxiant		
Hazards Not Otherwise Classified		

Version No: 5.1

Issue Date: 11/11/2019 Print Date: 17/11/2021

None Reported

#### State Regulations

### US. California Proposition 65

None Reported

### National Inventory Status

National inventory Status			
National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (5,5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	Yes		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	No (5,5'-dithiobis-1,3,4-thiadiazole-2(3H)-thione)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

**BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89** 

### **SECTION 16 Other information**

Revision Date	11/11/2019
Initial Date	28/06/2003

### **SDS Version Summary**

Version	Date of Update	Sections Updated
5.1	11/11/2019	Disposal, Fire Fighter (fire/explosion hazard), Physical Properties, Use

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limita

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

Chemwatch: 4076-06 Page 9 of 9 Issue Date: 11/11/2019 Version No: 5.1 Print Date: 17/11/2021

**BISLUBE EXTREME PRESSURE ANTI-WEAR DM 89** 

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.